Application Number Information

Application Number: 10/530370 Examiner Number: 80488 / TORRES, JUAN

Assignments

Filing or 371(c) Date: **09/19/2005** <u>eDan</u> Group Art Unit: **2611** IFW Madras

Effective Date: **04/05/2005** Class/Subclass: **375/346.000**

Application Received: 04/05/2005 Lost Case: NO

Pat. Num./Pub. Num: /20060014487 Interference Number:
Issue Date: 00/00/0000 Unmatched Petition: NO
Date of Abandonment: 00/00/0000 L&R Code: Secrecy Code:1

Attorney Docket Number: P16694US2 Third Level Review: NO Secrecy Order: NO

Status: 71 /RESPONSE TO NON-FINAL OFFICE ACTION ENTERED
Status Date: 08/30/2009


AND FORWARDED TO EXAMINER

Confirmation Number: 2983 Oral Hearing: NO

Title of Invention: METHOD AND DEVICE FOR ESTIMATING A SIGNAL TO

INTERFERENCE RATIO (SIR) IN WIDEBAND CODE DIVISION MULTIPLE ACCESS

(WCDMA) SYSTEMS



To go back, right click here and select Back. To go forward, right click here and select Forward. To refresh, right click here and select Refresh.

Back to OASIS | Home page

http://EXPOWEB1:8001/cgi-bin/expo/GenInfo/snquery.pl?APPL_ID=10530370

drjatorres@gmail.com | Web History | Settings → | Sign out



"tpc command" SiR verifying

Search

Advanced Search

Web Show options...

Results 1 - 10 o

IPDFI TSGR1#7bis(99)f87

File Format: PDF/Adobe Acrobat - View

SIR target then the TPC command to transmit is "0", while if. SIR est. < SIR target ... commands verify TPC_cmd=1. In such a case Δ . TPC. =2dB. If Δ ... ftp.3gpp.org/tsg ran/WG1 RL1/TSGR1 07b/.../R1-99f87.pdf - Similar - \Box [\Box] \Box

Best-Effort Macro Diversity - Patent - network node and a method ...
If the estimated SIR value is less than a SIR target 303 a TPC command UP is ... the SIR target 303 a further check is made 305 to verify if the required ...
www.faqs.org/patents/app/20090186617 - Cached - Similar - SIRIES

Show more results from www.freepatentsonline.com

Robust SIR Measurement Algorithm with Closed Loop Power Control in ... ment algorithm which can minimize the measured SIR off- set in wireless mobile channel environment and verify that. Manuscript received November 25, 2005. ... ietcom.oxfordjournals.org/cgi/reprint/E89-B/10/2819.pdf - Similar - ORDING NOVEMBER - OR

Abstract - ACTA Press • Scientific & Technical Publications ...

We **verify** the performance of the proposed algorithm by simulation. ... One is inner loop power control algorithm based on **SIR** measurement during a time slot. ... By using **TPC command** transmitted, BS adjusts its transmission power to the ...

www.actapress.com/PDFViewer.aspx?paperId=16841 - Similar - © 🔻 🗵 by H Park - Related articles - All 3 versions

Abstract - ACTA Press • Scientific & Technical Publications ...

The derivation of the binary **TPC command** sent every time slot (approxi-mately every ... The common target **SIR** is adjusted (or left unchanged) every 10 ms In the Appendix, we also **verify** the negative correla- tion for the case of n ...

www.actapress.com/PDFViewer.aspx?paperId=26160 - <u>Similar</u> - Similar - Vivial Similar - Viv

by B Rohani - 2006 - Cited by 1 - Related articles - All 4 versions

Radio communication system with adjustable output transmission ... If a received TPC command is "0" then the MS 110 reduces its received SIR, other properties of the received signal could be used to verify the decision ... www.patentstorm.us/patents/7079858/description.html - Similar - 🂝 📳 🗵

[PDF] Simulation Analysis of Adaptive Power Control Method in TD-SCDMA ... File Format: PDF/Adobe Acrobat - View

SIR-based power control may cause positive feedback, which can endanger the stability of

the system. ... detect SNR without synchronism, the TPC command will be In order to verify our algorithm in a convenient way, we ...

www.sys.virginia.edu/sieds07/papers/SIEDS07_0017_FLpdf - Similar - 💬 💹 🗵 by M Wang - 2007 - Related articles

| 1 2 | 3 4 5 6 7 | <u>8</u> <u>9</u> <u>10</u> | Next |
|--|------------------|-----------------------------|---------------------|
| Personalize | ed based on yo | our web histo | ry. <u>More det</u> |
| Add a result - See all my Sea | archWiki notes | - See all not | es for this S |
| | | | |
| "tpc command | ป" SiR verifyino | 9 | Sea |
| Search within results - Language Tools - | Search Help - | - Dissatisfied | ? Help us im |
| | | | |

drjatorres@gmail.com | Web History | Settings → | Sign out



"tpc command" SiR verification

Search Ad

Advanced Search

Web Show options...

Results 1 - 10 of a

[PDF] TSG-RAN Working Group 1(Radio) meeting #5 Cheju, Korea, 01 – 04 ... File Format: PDF/Adobe Acrobat - View Structure (a) may be used in conjunction with antenna verification. ... downlink SIR measurement. The TPC command field on the reverse uplink starts, ... Itb.3gpp.org/tsg_ran/WG1_RL1/TSGR1_05/.../r1-99595.pdf - Similar - (Command Field on the reverse uplink starts)

Abstract - ACTA Press • Scientific & Technical Publications ...

If the SIR is more than the target SIR+1, the TPC command "down" is sent to the UE ... 4.5

Verification and Validation One of the most important aspects in ...

www.actapress.com/PDFViewer.aspx?paperid=13231 - Similar - (**)

by S Chantaraskul - Cited by 5 - Related articles - All 3 versions

Method for reducing interference in a radio communication system ... When reducing the target SIR, the serving base station shall apply a local outer The base station would be able to reliably detect the TPC command, and HS-DPCCH on/off jointly, toggle HSDPA on/off (better for verification) ... www.freepatentsonline.com/EP1720264.html - Similar - (**) (**) (**) by A Klein - 2006 - All 2 versions

Show more results from www.freepatentsonline.com

Using Case-Based Reasoning in Traffic Pattern Recognition for Best ... SIR+1, the TPC command "down" is sent to the UE which ... model is its credibility; therefore the validation and verification of ... portal.acm.org/it_gateway.cfm?id=1023708&type=pdf - Similar - DEVICE by S Chantaraskui - 2004 - Cited by 2 - Related articles

Transmission power control target calculating apparatus - Patents ... verification is attached to transmission target data (data block) (ST1). The target SIR calculated by the target SIR_virtual calculating section 32 [0233]When the measured SIR is lower than the target SIR, a TPC command ... www.fags.org/patents/app/20080214230 - Cached - Similar -

Improvements in W-CDMA: principles and experimental results false detection, a verification mode is added by using a The measured sm is compared to the target SIR and the TPC command is generated, ... www.springerlink.com/index/6G92K1NW503750G7.pdf - Similar -

Physical Layer Chip Rate Processing

This **TPC command** is generated by comparing the DL **SIR** estimate with an **SIR** target, CPICH, combined using a priori and antenna **verification** knowledge. ...

doi.wiley.com/10.1002/0470861797.ch3 - Similar - (**) (**)

[PDF] 3GPP TS 25.214

File Format: PDF/Adobe Acrobat - View as HTML assignment message verification in a later phase in case of success. downlink SIR

measurement. The **TPC command** field on the uplink starts, ... www.mumor.org/public/background/25214-500.pdf - Similar - ② 添版

MG3681A

Controlling to equalize with target SIR. * Outer loop power control Set TPC command for Inner loop power control. » 60 TPC command (60 slots) ... www.eu.anritsu.com/files/MG3681A_EI1900.pdf - Similar - @ @ X

| | 1 2 3 4 5 6 7 8 9 10 | Next |
|-----------|--|---------------|
| | Add a result - See all my SearchWiki notes - See all note | es for this S |
| | | |
| | "tpc command" SiR verification | Se |
| <u>Se</u> | arch within results - Language Tools - Search Help - Dissatisfied? | ' Help us im |
| | Google Home - Advertising Programs - Business Solu | tions - Priv |

drjatorres@gmail.com | Web History | Settings → | Sign out



"tpc command" SiR verifying pilot data symbols

Search Advanced Search

Web Show options...

Results 1 - 10 of about 99 for "tpc

Robust SIR Measurement Algorithm with Closed Loop Power Control in ... only channel compensated pilot and data symbols in DPCH for SIR measurement; however, it has significant ... set in wireless mobile channel environment and verify that ... and the scrambled signal is amplified by the TPC command ... ietcom.oxfordjournals.org/cgi/reprint/E89-B/10/2819.pdf - Similar - COMMINION CONTROL OF THE SIMI

Method for reducing interference in a radio communication system ... When reducing the target SIR, the serving base station shall apply a local Example: 2 (4 in case of FBI) different pilot sequences (10 symbols long) are It could be advantageous to verify whether the HS-SCCH messages were ... it is no longer able to detect the TPC command for adjusting its own power. ... www.freepatentsonline.com/EP1720264.html - Similar - (10)

Show more results from www.freepatentsonline.com

Improvements in W-CDMA: principles and experimental results

Abstract - ACTA Press • Scientific & Technical Publications ...

The derivation of the binary **TPC command** sent every time slot (approxi- ... The common target **SIR** is adjusted (or left unchanged) every 10 ms ... decoded **data** and comparing with the sign bits of the channel **symbols**. In the Appendix, we also **verify** the negative correla- tion for the case of n = 2 BSs and m = 1. ... www.actapress.com/PDFViewer.aspx?paperid=26160 - Similar - Simila

"Radio System". In: W-CDMA

The **pilot symbols** in downlink are time-multiplexed with **data symbols**, detection, the **TPC command**, FeedBack Information (FBI) and the Transport Format and, as TPC bits, sends an "UP" command if it is below the target **SIR** or a "DOWN" tools for **verifying** the allocation of power and the amount of ... doi.wiley.com/10.1002/0470854642.ch3 - Similar -

2 GHz W-CDMA Radio Transceiver

Aug 16, 2009 ... The outer loop adjusts the target **SIR** based on the quality of the received signal. ... The **pilot symbols** associates in the both uplink and downlink as ... with the **TPC command** and the **data**; while the **pilot symbols** on the was performed to **verify** the

spurious response of the frequency plan. ...

[PDF] Characterization of Uplink Transmit Power and Talk Time in WCDMA ... File Format: PDF/Adobe Acrobat - View as HTML

Received Signal Code Power is defined as the received power on the **pilot** code after de-... target SIR, the BTS sends a TPC command "0" to the UE to reduce its transmit In order to **verify** the talk time experimental procedure in the **symbol** transitions through zero, which reduces the peak-to-average power ...

scholar.lib.vt.edu/theses/available/etd-08012008.../Arjun Thesis.pdf - Similar - 🗇 🐺 🔯 by AB Raju - 2008 - Cited by 3 - Related articles

Telecommunications inventions August - list RSS, inventions by ... A downlink frame has plural symbols into which pilot subcarriers are 20070184821 -Business process for disseminating pilot weather data by voice: A ... www.freshpatents.com/Telecommunications-dt200708ntc455.php -Cached - Similar - 💬 📳 🛞

[PDF] TIME DIVISION DUPLEX-WIDEBAND CODE DIVISION MULTIPLEX (TDD-WCDMA ...

File Format: PDF/Adobe Acrobat - View as HTML

In Figure 2, DwPTS represents a Downlink pilot time slot, UpPTS an Uplink code, where k denotes the modulation symbol time index. time slot in the second subframe, a TPC command has been reached to each user ... To verify the simulation setups, the QPSK results in this report were compared ...

www.ece.uic.edu/~eustunel/Eser Thesis TDD WCDMA0424.pdf - Similar - @ [\$1]\$ by E Ustunel - 2006 - All 2 versions

> 1 2 3 4 5 6 Next

Add a result - See all my SearchWiki notes - See all notes for this S

"tpc command" SiR verifying pilot data symbols

Search within results - Language Tools - Search Help - Dissatisfied? Help us im

drjatorres@gmail.com | Web History | Settings - | Sign out



"tpc command" SiR verifying pilot data symbols

Search

Advanced Search

Web Show options...

Results 11 - 20 of about 99 for "tpc

[PDF] 3GPP TS 25.214

File Format: PDF/Adobe Acrobat - View as HTML

For the closed loop mode 1 different orthogonal dedicated **pilot symbols** in the downlink **SIR** measurement. The **TPC command** field on the uplink starts, ... www.quintillion.co.jp/3GPP/Specs/25214-740.pdf - Similar - @2 @4 X

[PDF] 3GPP report skeleton

File Format: PDF/Adobe Acrobat

Spread and scrambled signal of **data symbols** and **data** blocks When the measured value is higher than the target **SIR** value, **TPC command** ='down'. ... www.arib.or.jp/IMT-2000/V730Jul09/5.../Rel4/.../25928-401.pdf - Similar · (C) | | | | | |

IPDFI 3GPP TS 25.214 (Rel-4)

File Format: PDF/Adobe Acrobat - View as HTML

For the closed loop mode 1 different orthogonal dedicated **pilot symbols** in the downlink **SIR** measurement. For the DPCH, the **TPC command** field on the ... www.arib.or.jp/IMT-2000/V730Jul09/2.../25/A25214-7b0.pdf - Similar - (**) (**) More results from www.arib.or.jp **

[PDF] Power Control for Mobile Radio Systems Using Perceptual Speech ...

File Format: PDF/Adobe Acrobat

SIR th. SIR threshold. txtpc cmd. Transmitted TPC command uses the pilot symbols on the control channel to estimate the downlink received SIR and ...

theses.library.uwa.edu.au/adt-WU2007.0174/public/02whole.pdf - Similar - > X X by BR MEHDIABADI - Related articles

High-Speed Downlink Packet Access

DATA. **PILOT**. 2560 chips. Figure 12.9. HS-DPCCH structure ... timing is thus quantised to 256 chips (**symbol** aligned) and minimum values as 7.5 slots using a common baseline received in the simulations so that multiple companies can **verify** ... when using different timing offsets, the **TPC command** stream ...

doi.wiley.com/10.1002/9780470512531.ch12 - Similar - 💬 🐺 🔀

Telecommunications inventions June - archived by invention type

The user equipment derives the **TPC command** error rate R to ad just. an inbound voice signal; outbound **data** into an outbound **data symbol** stream; an. ... www.freshpatents.com/Telecommunications-dt200806ntc455.php - Gached - Similar - Si

[PDF] 3GPP TS 25.214 V7.4.0 (2007-03)

File Format: PDF/Adobe Acrobat - View as HTML

For the closed loop mode 1 different orthogonal dedicated **pilot symbols** in the downlink **SIR** measurement. The **TPC command** field on the uplink starts, ... q-Lip/3GPP/Specs/25214-740.pdf - Similar - (2) (3)

ebook - The UMTS Network and Radio Access Technology

4.5.5 Spreading **Data Symbols** and **Data** Blocks It also describes the channel models used to **verify** and justify the performance for The **pilot** patterns are given Table 4.6

and the TPC bit pattern is given in Table 4.8. After deriving the combined **TPC** command TPC_cmd using one of the two supported ...

www.scribd.com/.../ebook-The-UMTS-Network-and-Radio-Access-Technology - Cached - Similar - (*) (*) (*)

[PDF] 3GPP TS 34.121 V6.0.0 (2005-03)

File Format: PDF/Adobe Acrobat

www.azouk.com/194929/no-title/download - Similar - WWW

IST-4-027310 MEMBRANE Deliverable D4.2.1 Joint Routing, Scheduling ... quality (eg, in terms of supportable **data** rate and **SIR**). Furthermore, taking into account **pilot symbols** and overheads, should be around 36 ...

www.imperial.ac.uk/membrane/documents/.../D4.2.1_final.pdf - Similar - @ [%] 🔯

| | Previous | 1 2 | 3 4 | 5 Next | |
|-------------------------------|--------------------------|---------|-----------------------|--------------------|--------|
| Add a result - Se | ee all my SearchW | 'iki no | <u>tes</u> - <u>S</u> | ee all notes for t | this S |
| "tpc cc | ommand" SiR verit | | | | |
| Search within results - Langu | uage Tools - <u>Sear</u> | ch He | lp - Dis | ssatisfied? Help | us im |

drjatorres@gmail.com | Web History | Settings - | Sign out



"tpc command" SiR verifying pilot data symbols

Search Advanced Search

Web Show options...

Results 21 - 30 of about 99 for "tpc

IPDFI COPYRIGHTED MATERIAL

File Format: PDF/Adobe Acrobat

which is send back to the network to **verify** a successful user Every bit of the **data** (**symbol**) stream will be spread (coded) by a number of code UE can now read the Common **Pilot** Channel, which is scrambled with one of eight primary ... < **SIR** target. →

TPC command "1". After reception of the TPC command, ...

3GPP TS 34.121

Definitions, **symbols**, abbreviations and equations used in the present To **verify** that the UE carrier frequency error does not exceed $\pm 0,1$ ppm. is the change in the UE transmitter output power in response to a single **TPC command**, is the number of **pilot** bits in the previously transmitted slot, and N ...

www.quintillion.co.jp/3GPP/Specs/34121-610.pdf - Similar - (*)

[PDF] WCDMA FOR UMTS Third Edition

File Formati PDF/Adobe Acrobat

correlator perform the despreading and integration to user **data symbols**. The channel. Figure 3.6. estimate the **SIR** from the **pilot** bits for each slot;. – send the **TPC command** in the downlink direction to the terminal to control its uplink to **verify** the origin and integrity of the messages. ...

cwc01.uwaterioo.ca/.../John.Wiley.and.Sons.WCDMA.for.UMTS.Radio.

Access.for.Third.Generation.Mobilemunications.Sep.2004.eBook-D... - Similar - (回答) 图

(PDF) 3GPP TS 25.101

File Format: PDF/Adobe Acrobat - View as HTML

This can be at a **TPC command** error ratio level of e.g. 30%. Power offsets of TFCI and **Pilot** fields relative to **data** field meaning that SCH is overlapping with the first **symbols** in DPCH in the beginning of DPCH slot structure. 040 1 R99 A test for UE's **SIR** target setting in a call set up ...

www.mumor.org/public/background/25101-520.pdf - Similar - @ | | | | | |

IPDFI TEAM FLY

File Format: PDF/Adobe Acrobat

how many chips are used to spread one **data symbol**. In the UTRAN, the then used to adjust the required **SIR** value. If the used **SIR** value still gives a There is no neutral **TPC command**; it is always either an increase or a **Pilot** pollution is a situation in which a mobile station receives several ...

[PDF] Evaluation Report for ETSI UMTS Terrestrial Radio Access (UTRA ...

File Format: PDF/Adobe Acrobat

of sources, may need additional review to **verify** compliance with the source documentation further Section Random access codes. I. Q. **Data** part. **Pilot symbols** **SIR** target,UL. → **TPC command** = "down". **SIR** est. < **SIR** target,UL ...

www.elo.utfsm.cl/~ipd465/.../evalutaion%2520utra.pdf - Similar - 💬 🎉 🛞

[PDF] TS 125 101 - V5.5.0 - Universal Mobile Telecommunications System ...

File Formati PDF/Adobe Acrobat

This can be at a **TPC command** error ratio level of e.g. 30%. Power offsets of TFCI and **Pilot** fields relative to **data** field meaning that SCH is overlapping with the first **symbols** in DPCH in the beginning of DPCH slot RP-000204 25.101 040 1 R99 A test for UE's **SIR** target setting in a call set up ...

[PDF] IST-4-027310 MEMBRANE Deliverable D4.2.2 Performance studies of ...

File Format: PDF/Adobe Acrobat

the known **pilot symbols** transmitted inside the **data** frame. In our simulation, using any **TPC command**. The procedure should be as follows: ...

www.imperial.ac.uk/membrane/documents/Deliverables/D4.2.2.pdf - Similar - Palated articles

[PDF] TS 125 101 - V4.2.0 - 3rd Generation Partnership Project ...

File Format: PDF/Adobe Acrobat

This can be at a **TPC command** error ratio level of e.g. 30%. Power offsets of TFCI and **Pilot** fields relative to **data** field meaning that SCH is overlapping with the first **symbols** in DPCH in the beginning of DPCH slot RP-000204 25.101 040 1 R99 A test for UE's **SIR** target setting in a call set up ...

tele1.dee.fct.unl.pt/csf_2003_2004/.../ts_125101v040200p.pdf - Similar - (\$\infty\) [\infty]

[PDF] ADAPTIVE POWER CONTROL IN CDMA CELLULAR COMMUNICATION SYSTEMS

File Format: PDF/Adobe Acrobat

number of **pilot** and/or **data symbols** and derives a **TPC command**. ... available **pilot** bits are used for **SIR** estimation, the averaging time of the To **verify** the results in a more realistic environment, the simulation program ...

lib.tkk.fi/Diss/2005/isbn9512278987/isbn9512278987.pdf - Similar - 💬 🖟 🔀 by M Rintamäki - Cited by 6 - Related articles

Previous 1 2 3 4 Next

Add a result - See all my SearchWiki notes - See all notes for this See

"tpc command" SiR verifying pilot data symbols

Search within results - Language Tools - Search Help - Dissatisfied? Help us im

| Web | Images | Videos | Maps | News | Shopping | Gmail | more * |
|-----|--------|--------|------|------|----------|-------|--------|
|-----|--------|--------|------|------|----------|-------|--------|

drjatorres@gmail.com | Web History | Settings → | Sign out



"tpc command" SiR verifying pilot data symbols

Search Advanced Search

Web Show options...

Results 31 - 34 of 34 for "tpc

[PDF] 3GPP TS 25.212

File Format: PDF/Adobe Acrobat

For the purposes of the present document, the following **symbols** apply: ... **SIR**. Signal-to-Interference Ratio. SNR. Signal to Noise Ratio. TF. Transport Format Thus there is only one **TPC command** flow and only one TFCI word in downlink **Pilot**. TFCI FBI TPC. Slot # (N first. – 1). **Data**. **Pilot**. TFCI FBI TPC ...

www.mumor.org/public/background/25212-500.pdf - Similar

[PDF] TS 125 212 - V4.3.0 - Universal Mobile Telecommunications System ...

File Format: PDF/Adobe Acrobat

For the purposes of the present document, the following **symbols** apply: the CFN **verifies** CFN mod Fmax = 0, where Fmax denotes the maximum number of radio ... Thus there is only one **TPC command** flow and only one TFCI word in downlink **Pilot**. TFCI FBI TPC. Slot # (Nfirst - 1). **Data**. **Pilot**. TFCI FBI TPC ...

www.azouk.com/184261/TS-125-212.../download - Similar

[APPLICATION] Method and device for estimating a signal to interference ratio ... - Google Paten

The relative power difference between the **data symbols** and the **pilot symbols** ... the steps of **verifying** a transmitted Transmit Power Control (**TPC**) **command**, ... www.google.com/patents?id=aMgaAAAAEBAJ - - »

[PDF] <u>차세대 휴대단말기 핵심 기술연구</u>

File Format: PDF/Adobe Acrobat

In order to **verify** and analysis the performance of Fig 2.2.8 Received **SIR** Value according to Various Power Control Algorithm ... Fig 2.3.54 **Symbol** Error Probability of The Channel Environment as Multi-User, **TPC command** **data**, TFCI, TPC, **pilot** field muxing physical channel **data**. 나) Spreading ...

register.itfind.or.kr/Report/200201/IITA/IITA.../IITA-0361.pdf - Similar by 최종 - Related articles

In order to show you the most relevant results, we have omitted some entries very similar to If you like, you can repeat the search with the omitted results included.

| | Previous 1 2 3 4 |
|----------------------|---|
| | |
| | "tpc command" SiR verifying pilot data symbols |
| Search within result | s - Language Tools - Search Help - Dissatisfied? Help us im |

drjatorres@gmail.com | Web History | Settings - | Sign out



"tpc command" SiR verifying pilot data symbols weighting

Search Advanced S

Web Show options...

Results 1 - 10 of about 87 for "tpc command"

Improvements in W-CDMA: principles and experimental results - 9:16am

The measured sm is compared to the target SIR and the TPC command is generated, weight updating using decision-feedback data symbols as well as pilot symbols, and pilot results from the reverse and forward links verify the ...

www.springerlink.com/index/6G92K1NW503750G7.pdf - Similar - (**) ** (**) by M Sawahashi - 2001 - Cited by 5 - Related articles

Power control circuit and radio transmission apparatus - Patent ...
Feb 26, 2008 ... The control **data** has respective regions of a **pilot symbol** (**Pilot**) ... and the **TPC command** thereof increases or decreases transmission power ...
www.freepatentsonline.com/7336751.html - Similar - Similar

Telecommunications inventions August - list RSS, inventions by ...
A downlink frame has plural **symbols** into which **pilot** subcarriers are 20070184821 - Business process for disseminating **pilot** weather **data** by voice: A ... www.freshpatents.com/Telecommunications-dt200708ntc455.php - Cached - Similar - Reference of the communications of th

Telecommunications inventions June - archived by invention type
The method includes determining a weight set for maximizing a data rate among at cell
and adjacent cells based on pilot symbols for used in handover. ...
www.freshpatents.com/Telecommunications-dt200806ntc455.php Cached · Similar · (**) ***

Cached · Similar · (**) ***

Show more results from www.freshpatents.com

[PDF] Characterization of Uplink Transmit Power and Talk Time in WCDMA ...

File Format: PDF/Adobe Acrobat - View as HTML

Received Signal Code Power is defined as the received power on the **pilot** code after de-... target **SIR**, the BTS sends a **TPC command** "0" to the UE to reduce its transmit power. **weighing** the **data** collected in all the locations which might not be In order to **verify** the talk time experimental procedure in the ...

scholar.lib.vt.edu/theses/available/etd-08012008.../Arjun_Thesis.pdf - Similar - © 📳 🗵 by AB Raju - 2008 - Cited by 3 - Related articles

W-CDMA and Cdma2000 for 3gmobilenetworks

The **symbols** of the I and Q branches are multiplied by a gain factor and On receiving a **TPC command**, the 222 Slot N-1 Slot N **Pilot Data** TPC TFCI **Data** ...

www.scribd.com/.../WCDMA-and-Cdma2000-for-3GMobileNetworks - Cached - Similar - 💬 🔣 🗵

ebook - The UMTS Network and Radio Access Technology

4.5.5 Spreading **Data Symbols** and **Data** Blocks It also describes the channel models used to **verify** and justify the performance for the Channelization and **weighting** follows the same pattern as in the PRACH. After deriving the combined **TPC command** TPC_cmd using one of the two supported algorithms ...

www.scribd.com/.../ebook-The-UMTS-Network-and-Radio-Access-Technology -

Cached - Similar - @ (\$) |X|

Show more results from www.scribd.com

[PDF] 3GPP report skeleton

File Format: PDF/Adobe Acrobat

Spread and scrambled signal of **data symbols** and **data** blocks When the measured value is higher than the target **SIR** value, **TPC command** ='down'. ...

www.arib.or.jp/IMT-2000/V730Jul09/5.../Rel4/.../25928-401.pdf - Similar - @ | | | | | |

[PDF] 3GPP TS 25.214

File Format: PDF/Adobe Acrobat - View as HTML

For the closed loop mode 1 different orthogonal dedicated **pilot symbols** in the downlink **SIR** measurement. The **TPC command** field on the uplink starts, ...

www.quintillion.co.jp/3GPP/Specs/25214-740.pdf - Similar - 💮 🦹

"Radio System". In: W-CDMA

The **pilot symbols** in downlink are time-multiplexed with **data symbols**, detection, the **TPC command**, FeedBack Information (FBI) and the Transport Format In the figure, β is the gain factor, which refers to the **weight** tools for **verifying** the allocation of power and the amount of interference. ...

doi.wiley.com/10.1002/0470854642.ch3 - Similar - (1) (2) (2)

1 2 3 4 5 6 Next

Add a result - See all my SearchWiki notes - See all notes for this S

"tpc command" SiR verifying pilot data symbols weighting

Search within results - Language Tools - Search Help - Dissatisfied? Help us im

drjatorres@gmail.com | Web History | Settings → | Sign out



"tpc command" SiR verifying pilot data symbols weighting

Search

Advanced S

Web Show options...

Results 11 - 20 of about 87 for "tpc command"

[PDF] 3GPP TS 25.214 (Rel-4)

File Format: PDF/Adobe Acrobat - View as HTML

For the closed loop mode 1 different orthogonal dedicated **pilot symbols** in the downlink **SIR** measurement. For the DPCH, the **TPC command** field on the ... www.arib.or.jp/IMT-2000/V730Jul09/2.../25/A25214-7b0.pdf - Similar - Sim

Enhanced Wireless Access Technologies and Experiments for W-CDMA ... Periodically received **pilot symbols** and tentatively decided **data symbols** after The transmitted **SIR** of MS1 before **weighting** was –5, –10, and –12 dB. ... www.comsoc.org/pci/private/2000/dec/sawahashi.html - Similar - © [8] [8]

[PDF] IST-4-027310 MEMBRANE Deliverable D4.2.2 Performance studies of ...

File Format: PDF/Adobe Acrobat

the known **pilot symbols** transmitted inside the **data** frame. In our simulation, using any **TPC command**. The procedure should be as follows: ...

www.imperial.ac.uk/membrane/documents/Deliverables/D4.2.2.pdf - Similar - PRINT By M Kuzminskiy - Related articles

JPDFI ADAPTIVE POWER CONTROL IN CDMA CELLULAR COMMUNICATION SYSTEMS

File Format: PDF/Adobe Acrobat

number of **pilot** and/or **data symbols** and derives a **TPC command**. ... available **pilot** bits are used for **SIR** estimation, the averaging time of the that the **weighting** helps to reduce the variance of the PC command before relay. To **verify** the results in a more realistic environment, the simulation program ...

lib.tkk.fi/Diss/2005/isbn9512278987/isbn9512278987.pdf - Similar - © 📳 🔀 by M Rintamäki - Cited by 6 - Related articles

"The UTRA Physical Layer Design". In: The UMTS Network and Radio ... Likewise after the weighting, we sum the stream of real- to the following rules: if SIR est. > SIR target then the TPC command enables We can use the shadowed part of the pilot symbol pattern illustrated in Table 4.23 as ... transmit diversity, STTD encoding applies to the S-CCPCH data symbols. ...

doi.wiley.com/10.1002/0470841729.ch4 - Similar - @ 图 图

[PDF] TEAM FLY

File Format: PDF/Adobe Acrobat

3.1.11 Power **Weighting** and Combining of Physical Channels how many chips are used to spread one **data symbol**. In the UTRAN, the There is no neutral **TPC command**; it is always either an increase or a decrease command. **Pilot** pollution is a situation in which a mobile station receives several **pilot** ...

www.elib.hbi.ir/.../1580535070-Artech-Introduction%20to%203G%20Mobile% 20Communications%202ed... - Similar - (18)

[PDF] WCDMA FOR UMTS Third Edition

File Format: PDF/Adobe Acrobat

11.1 Release '99 WCDMA Downlink Packet **Data** Capabilities well as the instantaneous channel state as **weighted** complex phasors. To facilitate point 2,. WCDMA uses known **pilot symbols** that are used to sound the channel and provide an send the **TPC**

command in the downlink direction to the terminal to ...

www.supcom.mincom.tn/.../John.Wiley.and.Sons.WCDMA.for.UMTS.Radio. Access.for.Third.Generation.Mobile.Communications.Sep.2004.eBo... - Similar - 💬 🐺 😿

[PDF] Evaluation Report for ETSI UMTS Terrestrial Radio Access (UTRA ...

File Format: PDF/Adobe Acrobat

of sources, may need additional review to **verify** compliance with the source documentation. further Section Random access codes. I. Q. **Data** part. **Pilot symbols** **SIR** target,UL. → **TPC command** = "down". **SIR** est. < **SIR** target,UL test cases the vector alpha contains the **weight** factors for the **pilot** ...

www.elo.utfsm.cl/~ipd465/.../evalutaion%2520utra.pdf - Similar - @ (※) ※

IPDFI SAWAHASHI LAYOUT

File Format: PDF/Adobe Acrobat - View as HTML
Coherent Channel Estimation and SIR-Based Fast TPC. Pilot symbol assisted (PSA) coherent In the transmitter, the coded data are weight-multiplied in ...
www.azouk.com/162868/SAWAHASHI-LAYOUT/download - Similar - PRINCE

Previous 1 2 3 4 5 6 Next

🕭 Add a result - See all my SearchWiki notes - See all notes for this S

"tpc command" SiR verifying pilot data symbols weighting

Search within results - Language Tools - Search Help - Dissatisfied? Help us im

drjatorres@gmail.com | Web History | Settings → | Sign out



"tpc command" SiR verifying pilot data symbols weighting

Search | Advanced S

Web Show options...

Results 21 - 30 of about 87 for "tpc command"

3G TR 25.928

3G TR 25.928. V2.0.0. (2001-03). Technical Report. 3 rd. Generation Partnership Project (3GPP);. Technical Specification Group (TSG); ...

[PDF] 3G TR 25.928

File Format: PDF/Adobe Acrobat - View as HTML

3G TR 25.928. V1.1.0 2. (2000-07). Technical Report. 3 rd. Generation Partnership Project (3GPP); Technical Specification Group (TSG); ...

3GPP TR 25.928

3GPP TR 25.928. V4.0.1. (2001-03). Technical Report. 3rd Generation Partnership Project;. Technical Specification Group (TSG);. Radio Access Network (RAN); ... www.quintillion.co.jp/3GPP/Specs/25928-401.pdf - Similar - (2014) (2014)

Untitled

www.itks-training.com:8888/.../Wiley.The.Next.Generation.CDMA. Technologies.Sep.2007.pdf - Similar - (2014)

[PDF] www.GetPedia.com

File Format: PDF/Adobe Acrobat - View as HTML

Library of Congress Cataloging-in-Publication **Data**. A catalogue record from the Library of Congress has ... British Library Cataloguing in Publication **Data** ...

sodaphish.com/.../(EBOOK%20-%20ENG%20-%20TELECOMUNICAZIONI)%20Wiley%20-... - Similar - (**) ** (**)

[DOC] IEEE P802.22 DRAFT Version 1.1

File Format: Microsoft Word - View as HTML

The MAC data elements from Figure 12, starting from the FCH and including the first broadcast burst, are entered into the second OFDM symbol, ...

research.microsoft.com/en-us/um/people/../802.22 draftv1.1.doc - Similar - @ | 🔻 | 🗵

[PDF] ADAPTIVE POWER CONTROL IN CDMA CELLULAR COMMUNICATION SYSTEMS

File Format: PDF/Adobe Acrobat - View as HTML

power control misadjustment (error between measured **SIR** and **SIR** target) at The 2G systems have evolved further to provide also packet-switched **data** ...

www.azouk.com/195094/no-title/download - Similar - @ 74 18

Approvals (get approvals from document manager)

attach.baisi.net/getattach.php?a:::Alcatel+-+Umts... - Similar - (**)

WCDMA FOR UMTS Third Edition

14.4.1 Uplink Data Transmission. 438. 14.4.2 Downlink Data Transmission. 439. 14.4.3

Channel Coding for User **Data**. 440. 14.5 Signalling. 441. 14.5.1 **Pilot ...** rustamefendi.files.wordpress.com/2008/05/wcdma-for-umts.pdf - Similar - Simila

[PDF] W-CDMA

File Format: PDF/Adobe Acrobat - <u>View as HTML</u> expansion of **data** communications on a global scale—spearheaded by the Internet—is ... high-speed **data** communications capable of supporting mobile multimedia ... www.wsfamily.idv.tw/weng/wlan/wcdma-3.pdf - <u>Similar</u> · (**)

| Previous | 1 | 2 | 3 | <u>4</u> <u>5</u> | | Next | |
|---|---------|--------|------------------|-------------------|-----------------|---------|------------------|
| Add a result - See all my SearchV | Vik | i nc | otes | - See | all n | otes fo | or this S |
| | | ****** | ******** | ************* | | | |
| "tpc command" SiR verifying | pil | ot c | data | symb | ools v | veighti | ng |
| Search within results - Language Tools - Sear | rch | Нє | elp - | Dissa | <u>atisfi</u> e | ed? He | lp us im |
| Google Home - Advertising Pro | gra | ams | s - <u>B</u> | usine | ss S | olution | <u>s - Priva</u> |

drjatorres@gmail.com | Web History | Settings - | Sign out



"tpc command" SiR verifying pilot data symbols weighting

Search | Advanced S

Web Show options...

Results 31 - 36 of 36 for "tpc command"

Introduction to 3G Mobile Communications

3.1.11 Power **Weighting** and Combining of Physical Channels digital multimedia handsets with high **data** transmission rates, capable of ... amitbd.com/.../Artech.House.Introduction.To.3G.Mobile.Communications.2nd.Edition.pdf -

Untitled

Similar

Frequently Used **Symbols**. 124. 4.2 Transport Channels, Formats and Combinations Transparent mode **data**. TMP. Time multiplexed **pilot** ... freebookvn.com/download.php?file...pdf - Similar

Next Generation Mobile Systems: 3G and Beyond

Library of Congress Cataloging-in-Publication **Data** 4.3.1 Higher **Data** Rates and Low Power Consumption 107 ...

www.cfcqc.com/zldown/6%5C下一代移动通讯系统3G展望.pdf · Similar

"vielfachzugriff im codemultiplex": English dictionary translation ... - [Translate this page] ... wherein said verifying comprisesweighting said pilot and data symbols, anddetermining if said TPC command has been correctly received, andgiving a SIR ... www.linguee.com/de.../vielfachzugriff+im+codemultiplex.html - Cached - Similar

[PDF] 차세대 휴대단말기 핵심 기술연구

File Format: PDF/Adobe Acrobat

In order to **verify** and analysis the performance of Fig 2.2.8 Received **SIR** Value according to Various Power Control Algorithm ... Fig 2.3.54 **Symbol** Error Probability of The Channel Environment as Multi-User, **TPC command data**, TFCI, TPC, **pilot** field muxing physical channel **data**. 中) Spreading ...

register.ltfind.or.kr/Report/200201/IITA/IITA.../IITA-0361.pdf - <u>Similar</u> by 최종 - Related articles

[PDF] TEAMFLY

File Format: PDF/Adobe Acrobat - View as HTML

Within each slot **data**. Transport Format Combination Indication (TFCI) field and **pilot** files are inserted and that is the key for the main difference between ...

book.dlf.ge/.../J.Wiley%20&%20Sons%20-%20Broadband%20Wireless%20Mobile%203G%20And%20Beyon... - Similar

In order to show you the most relevant results, we have omitted some entries very similar to If you like, you can repeat the search with the omitted results included.

Previous 1 2 3 4

| Page 2 of 2 | tpc command" SiR verifying pilot data symbols weighting - Google Search |
|------------------------|---|
| | |
| | |
| | |
| mbols weighting | "tpc command" SiR verifying pilot data symbo |
| ssatisfied? Help us im | Search within results - Language Tools - Search Help - Dissati |
| | |

drjatorres@gmail.com | Web History | Settings - | Sign out



"tpc command" SiR verifying pilot data symbols weights estimating

Search

Web Show options...

Results 1 - 10 of about 48 for "tpc command" SiR veri

Improvements in W-CDMA: principles and experimental results - 9:16am
The measured sm is compared to the target SIR and the TPC command is generated, which is transmitted to rive channel estimation (ICE) using both pilot and deci-..... weight updating using decision-feedback data symbols SIR is -12 dB. These results from the reverse and forward links verify the ...

www.springerlink.com/index/6G92K1NW503750G7.pdf - Similar - DEX by M Sawahashi - 2001 - Cited by 5 - Related articles

Method and device for estimating a signal to interference ratio ...
The relative power difference between the data symbols and the pilot symbols ... Power Control (TPC) command, and giving a SIR estimation depending on the ...
www.freshpatents.com/Method-and-device-for-estimating-a-signal-to-interference-ratio-sir-in-wcdma-systems-dt20060119ptan2006001... - Similar - Simila

Method and device for **estimating** a signal to interference ratio ...
This results in an inaccurate **SIR estimation** and causes also high [0044] which only uses **pilot** and **data symbols** after the transmitted power change. ...
www.freshpatents.com/Method-and-device-for-estimating-a-signal-to-interference-ratio-sir--in-wcdma-systems-dt20060119ptan2006001... - Similar -

Show more results from www.freshpatents.com

Adaptive Power Control in CDMA Cellular Communication Systems
The weights are updated using some adaptive algorithm such as the Recursive If the delays due to SIR estimation and TPC command processing are longer, ... SIR γ(t) over a number of pilot and/or data symbols and derives a TPC command. To verify the results in a more realistic environment, the simulation ...

www.scribd.com/.../Adaptive-Power-Control-in-CDMA-Cellular-Communication-Systems - Cached - Similar - (*) (*) (*)

"Radio System". In: W-CDMA

The **pilot symbols** in downlink are time-multiplexed with **data symbols**, detection, the **TPC command**, FeedBack Information (FBI) and the Transport Format In mode 1, if UE can **estimate** the **weight** vector generated at the tools for **verifying** the allocation of power and the amount of interference. ...

doi.wiley.com/10.1002/0470854642.ch3 - Similar - 💮 🐺 🕅

"The UTRA Physical Layer Design". In: The UMTS Network and Radio ... in the active set estimate signal-to-interference ratio (SIR ... to the following rules: if SIR est. > SIR target then the TPC command enables number of bits in the TPC and pilot fields, where symbol repetition fills up the fields transmit diversity, STTD encoding applies to the S-CCPCH data symbols. ...

doi.wiley.com/10.1002/0470841729.ch4 - <u>Similar</u> - 🏻 📳

| rener | 3GPP | report | skeleton |
|-------|---------|--------|----------|
| THUTT | ا وربوب | 100000 | SNOIGION |

File Format: PDF/Adobe Acrobat

Spread and scrambled signal of **data symbols** and **data** blocks When the measured value is higher than the target **SIR** value, **TPC command** ='down'. ...

www.arib.or.(p/IMT-2000/V730Jul09/5.../Rel4/.../25928-401.pdf - Similar - ② [劉 國

[PDF] 3GPP TS 25.214

File Format: PDF/Adobe Acrobat - View as HTML

dtx_drx_mode=0, UTRAN shall **estimate** the transmitted **TPC command** TPC For the closed loop mode 1 different orthogonal dedicated **pilot symbols** in the ...

www.quintillion.co.jp/3GPP/Specs/25214-740.pdf - Similar - @ IX IX

IST-4-027310 MEMBRANE Deliverable D4.2.1 Joint Routing, Scheduling ... quality (eg, in terms of supportable **data** rate and **SIR**). Furthermore, taking into account **pilot symbols** and overheads, should be around 36 ...

www.imperial.ac.uk/membrane/documents/.../D4.2.1 final.pdf - Similar - @ | | | | | | | | |

| | | 1 <u>2 3 4</u> | Next |
|------|----------------------------------|--------------------------------|-------------------------|
| | Add a result - See all my | SearchWiki notes - S | ee all notes for this S |
| | | | |
| | "tpc command" SiR verif | ying pilot data symbo | s weights estimating |
| Sear | ch within results - Language Toc | ols - <u>Search Help</u> - Dis | ssatisfied? Help us im |
| | | | |

drjatorres@gmail.com | Web History | Settings → | Sign out



"tpc command" SiR verifying pilot data symbols weights estimating

Search

Web Show options...

Results 11 - 20 of about 47 for "tpc command" SiR veri

ebook - The UMTS Network and Radio Access Technology

4.5.5 Spreading **Data Symbols** and **Data** Blocks It also describes the channel models used to **verify** and justify the performance for After channelization, gain factor bc for the control part and bd for the **data** part **weight** the After deriving the combined **TPC command** TPC_cmd using one of the two ...

www.scribd.com/.../ebook-The-UMTS-Network-and-Radio-Access-Technology - Cached - Similar - (2018) (80)

[PDF] 3GPP TS 25.214 (Rel-4)

File Format: PDF/Adobe Acrobat - View as HTML

After **estimating** the k:th **TPC command**, UTRAN shall adjust the current For the closed loop mode 1 different orthogonal dedicated **pilot symbols** in the ... www.arib.or.jp/IMT-2000/V730Jul09/2.../25/A25214-7b0.pdf - Similar - (2) (4) (3)

[PDF] IST-4-027310 MEMBRANE Deliverable D4.2.2 Performance studies of ...

File Format: PDF/Adobe Acrobat

square noise level in that channel. The channel **estimation** at the receiver is enabled by the known **pilot symbols** transmitted inside the **data** frame. ...

www.imperial.ac.uk/membrane/documents/Deliverables/D4.2.2.pdf - Similar - William by M Kuzminskiy - Related articles

(PDF) TEAM FLY

File Format: PDF/Adobe Acrobat

how many chips are used to spread one **data symbol**. In the UTRAN, the There is no neutral **TPC command**; it is always either an increase or a decrease command. ... UTRAN to set different **weights** on different channels according to their The UE uses the base station's common **pilot** channels to **estimate** the ...

[PDF] WCDMA FOR UMTS Third Edition

File Format: PDF/Adobe Acrobat

11.1 Release '99 WCDMA Downlink Packet **Data** Capabilities such as **SIR estimation** and outer loop power control, that are not needed in IS-95 mobiles. estimator uses the **pilot symbols** for **estimating** the channel state which will then send the **TPC command** in the downlink direction to the terminal to ...

www.supcom.mincom.tn/.../John.Wiley.and.Sons.WCDMA.for.UMTS.Radio. Access.for.Third.Generation.Mobile.Communications.Sep.2004.eBo... - <u>Similar</u> - © 🖹 🗵

[PDF] Evaluation Report for ETSI UMTS Terrestrial Radio Access (UTRA ...

File Format: PDF/Adobe Acrobat

in the current frequency band and generate a **SIR estimate SIR** ... Upon the reception of a **TPC command**, the mobile station should adjust the transmit power of both the consist of two **data symbol** fields, a midamble and a guard period. test cases the vector alpha contains the **weight** factors for the **pilot** ...

www.elo.utfsm.cl/~ipd465/.../evalutaion%2520utra.pdf - Similar - @/@/@/

Approvals (get approvals from document manager)

| 3.2.2.2 CPICH – Common Pilot channel |
|--|
| attach.baisi.net/getattach.php?a=Alcatel+-+Umts <u>Similar</u> - 💬 🗏 🗵 |
| File Format: PDF/Adobe Acrobat - View as HTML expansion of data communications on a global scale—spearheaded by the Internet—is high-speed data communications capable of supporting mobile multimedia www.wsfamily.idv.tw/weng/wlan/wcdma-3.pdf - Similar - File Research |
| Untitled Frequently Used Symbols. 124. 4.2 Transport Channels, Formats and Combinations Transparent mode data. TMP. Time multiplexed pilot freebookvn.com/download.php?filepdf - Similar - PIEI |
| Next Generation Mobile Systems: 3G and Beyond Library of Congress Cataloging-in-Publication Data 4.3.1 Higher Data Rates and Low Power Consumption 4.3.5 Location Estimation by WLAN www.cfcqc.com/zldown/6%5C下—代移动通讯系统3G展望.pdf - Similar - 〇 图 图 |
| Previous 1 2 3 Next |
| Add a result - See all my SearchWiki notes - See all notes for this See all my SearchWiki notes - See all notes for this See all my SearchWiki notes - See all notes for this See all my SearchWiki notes - See all notes for this See all my SearchWiki notes - See all notes for this See all my SearchWiki notes - See all notes for this See all my SearchWiki notes - See all notes for this See all my SearchWiki notes - See all notes for this See all notes for th |

Google Home - Advertising Programs - Business Solutions - Priva

"tpc command" SiR verifying pilot data symbols weights estimating

Search within results - Language Tools - Search Help - Dissatisfied? Help us im

drjatorres@gmail.com | Web History | Settings → | Sign out



"tpc command" SiR verifying pilot data symbols weights estimating

Search

Web Show options...

Results 21 - 21 of 21 for "tpc command" SiR veri

[PDF] 차세대 휴대단말기 핵심 기술연구

File Format: PDF/Adobe Acrobat

IMT2000 Transeiver Block-level Simulation and Performance **estimation** Fig 2.2.8 Received **SIR** Value according to Various Power Control Algorithm ... Fig 2.3.54 **Symbol** Error Probability of The Channel Environment as **TPC command** **data**, TFCI, TPC, **pilot** field muxing physical channel **data**. 나) Spreading ... register.itfind.or.kr/Report/200201/IITA/IITA.../IITA-0361.pdf - Similar - 등 图 文本 - Related articles

In order to show you the most relevant results, we have omitted some entries very similar to If you like, you can repeat the search with the omitted results included.

Previous 1 2 3

Add a result - See all my SearchWiki notes - See all notes for this Se

"tpc command" SiR verifying pilot data symbols weights estimating

Search within results - Language Tools - Search Help - Dissatisfied? Help us im



Home | Login | Logout | Access Information | Alerts | Purchase History |

Welcome United States Patent and Trademark Office

Search Results

BROWSE

SEARCH

IEEE XPLORE GUIDE

Results for "((tpc command and sir and pilot and data and symbols and weighting)<in>metadata)"

Your search matched 0 of 2392400 documents.

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.



» Search Options

View Session History

New Search

» Key

IEEE Journal or IEEE JNL

Magazine

RET JNE. IET Journal or Magazine

AIP JNL AIP Journal

AVS JNL **AVS Journal**

IEEE Conference IEEE ONF

Proceeding

SET ONF IET Conference

Proceeding

IEEE STD IEEE Standard

Indicates open access

content

Modify Search

((tpc command and sir and pilot and data and symbols and weighting)<in>metadata)

Search

Check to search only within this results set

Display Format: @ Citation @ Citation & Abstract

IEEE/IET/AIP/AVS Books **Educational Courses** Δ

IEEE/IET journals, transactions, letters, magazines, conference proceedings, AIP/ standards.

🚅 view selected items

Select All Deselect All

No results were found.

Please edit your search criteria and try again. Refer to the Help pages if you need assistan

indicated by 🗓 Inspeci Help Contact Us

@ Copyright 20

Saurch

IEEE XPLORE GUIDE

Educational Courses



Home | Login | Logout | Access Information | Alerts | Purchase History |

SEARCH

Welcome United States Patent and Trademark Office

Search Results

Your search matched 3 of 2392400 documents.

Results for "((tpc command and sir)<in>metadata)"

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.



» Search Options

View Session History

New Search

» Key

IEEE JNL IEEE Journal or

Magazine

IET Journal or Magazine IET JNL

AIP JNL AIP Journal

AVS JNL **AVS Journal**

IEEE Conference IEEE ONF

Proceeding

JET ONF **IET Conference**

Proceeding

MEEE STD IEEE Standard

Indicates open access

content

Modify Search

((tpc command and sir)<in>metadata)

Check to search only within this results set

BROWSE

Display Format: @ Citation @ Citation & Abstract

IEEE/IET journals, transactions, letters, magazines, conference proceedings, AIP/

standards.

ட view selected items إ

IEEE/IET/AIP/AVS

Select All Deselect All

Books

Optimum TPC command sequence in WCDMA

Chen Chaoyang; Liu Baoling; Quan qingyi; Zhang Ping;

Info-tech and Info-net, 2001. Proceedings. ICII 2001 - Beijing. 2001 Internatio

Volume 2, 29 Oct.-1 Nov. 2001 Page(s):134 - 138 vol.2 Digital Object Identifier 10.1109/ICII.2001.983566

AbstractPlus | Full Text: PDF(339 KB) ISSE ONE

Rights and Permissions

2 Closed-loop power control algorithms in soft handov systems

Grandell, J.; Salonaho, O.;

Communications, 2001. ICC 2001. IEEE International Conference on

Volume 3, 11-14 June 2001 Page(s):791 - 795 vol.3 Digital Object Identifier 10.1109/ICC.2001.937347

AbstractPlus | Full Text: PDF(368 KB) 1888 CNS

Rights and Permissions

3. On TPC decoding during soft handover in WCDMA

Lindoff, B.; Bernhardsson, B.;

Vehicular Technology Conference, 2005, VTC 2005-Spring, 2005 IEEE 61st

Volume 3, 30 May-1 June 2005 Page(s):1609 - 1613 Vol. 3 Digital Object Identifier 10.1109/VETECS.2005.1543592

AbstractPlus | Full Text: PDF(2232 KB) ISSE ONF

Rights and Permissions

Help Contact Us

@ Copyright 20



SCITUS for scientific information only

Advanced search | Preferences

| | Email, | Save or Export checked results | Sor |
|--|--|---|---------------------------------------|
| Filter search results by |] 1. <u>Met</u> r | hod and device for estimating a Signal to Interference Rasson, Elias (TELEFONAKTI EBOLAGET LM ERICSSON | atio (S |
| Content sources | 2004 | 4 | (|
| Journal sources | m | no: EP1408635 ethod for estimating a signalinterference ratio SIR of | |
| Preferred web (3) Patent Offices (3) | whe | a symbols, characterisedsteps of:(verifying (5.40) a rein said verifying comprises weighting said pilot and c ermininggiving a SIR estimationcharacterised by est | data s |
| Other web (1) | Full | text available at patent office. For more in-depth s | |
| File types * HTML (3) * PDF (1) | WCE JON | ETHOD AND DEVICE FOR ESTIMATING A SIGNAL TO INT DMA SYSTEMS ISSON, Elias (TELEFONAKTIEBOLAGET LM ERICSSO TATY APPLICATION, Apr 2004 | |
| Ů Refine your search | | no: WO04034614 | |
| power control mobile unit transmitted power code division transmission power wireless communication inner loop | the alwa pilo com Full | e sent data bits areuseful in estimating a more precipilot and data symbols are given equal weights and taysmethod for estimating a signalinterference ratio t and data symbols, characterisedsteps of verifying imand, and giving text available at patent office. For more in-depth star results | he sen (SIR) (5.40) |
| ■ channel changes ■ wideband ■ 10530370 more ▷ | Jons Jan patnus sym estir the s sign aC Full | hod and device for estimating a signal to interference rates son, Elias, UNITED STATES PATENT AND TRADEMARK 2006 no: US20060014487 seful in estimating a more precise SIR. Howeverestimations are given equal weights and the sent TPC commationon the TPC data, but in realitysteps of verify symbolsmethod for estimating a signalinterference alcomprising pilot and data symbols, characterisedControl (TPC) command, and giving text available at patent office. For more in-depth star results | nates of and is ring a terrationsteps |
| | Jun Fiç CQI [http | osoft Word - D4.2.1 final.doc [PDF-792K] 2007 gure 5-10 OFDM/IOTA and conventional OFDM spectra data processing delay p://www.imperial.ac.uk/membrane/documents/Deliverab lar results | |
| | Email, S | Save or Export checked results | |
| | Sponsored | llinks | |
| | Accubid Es Estimatin www.accu | g Software Made by Contractors for Contractors | |
| | <u>Digitizers f</u> | for Estimators | |

All Trades: Toll-free 800-731-3038 Take-Off Blueprints / CD's / PDF's

www.soltechs.com

Estimating Services

Conceptual, Design Dev., Bid Docs. N.E. throughout S.E. United States

www.outsource-psi.com

"tpc command" SiR verifying pilot data syn

Search

Downloads | Submit website | Scirus newsletter | Help | Library partners | Contact us

About us | Advisory board | Privacy policy | Terms & Conditions | Newsroom

Powered by FAST © Elsevier 2009

SCITUS for scientific information only

Advanced search | Preferences

| 1-1 of 1 hits for "tpc comman | d" SiR verifying pilot data symbols weighting estimating |
|---|--|
| | Email, Save or Export checked results Sor |
| Filter search results by | 1. Method and device for estimating a Signal to Interference Ratio (Si Jonsson, Elias (TELEFONAKTIEBOLAGET LM ERICSSON (publ |
| Content sources | 2004 |
| Journal sources | patno:EP1408635 means 50 for SIR method for estimating a signalinterferenc |
| Preferred web (1) Patent Offices (1) | signalcomprising pilot and data symbols, characterisedsteps aPower Control TPC command, wherein said verifying compris and data symbols, and determining if said TPC command has be |
| Other web | estimationcharacterised by estimating interference Full text available at patent office. For more in-depth search |
| File types | similar results |
| R HTML (1) | Email, Save or Export checked results |
| Ů Refine your search | Sponsored links |
| ep1408635 epa02022734 epb02022734 02022734 power control mobile unit transmitted power code division transmission power wireless communication | Accubid Estimating Estimating Software Made by Contractors for Contractors www.accubid.com Digitizers for Estimators All Trades: Toll-free 800-731-3038 Take-Off Blueprints / CD's / PDF's www.soltechs.com |
| more > | Estimating Services Conceptual, Design Dev., Bid Docs. N.E. throughout S.E. United States |

www.outsource-psi.com

| "tpc command" SiR verifying pilot data symbols weighting estimating results on scirus.co Page 2 of 2 |
|--|
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| 2 |
| "tpc command" SiR verifying pilot data syn, Search |
| |
| |
| |
| Downloads Submit website Scirus newsletter Help Library partners Contact us |
| About us Advisory board Privacy policy Terms & Conditions Newsroom |
| Powered by FAST © Elsevier 2009 |

SCITUS for scientific information only

Advanced search | Preferences

| 1-1 of 1 hits for "tpc comman | d" SiR verifying pilot data symbols weighting |
|---|---|
| | Email, <u>Save</u> or <u>Export</u> checked results Sol |
| Filter search results by | 1. Method and device for estimating a Signal to Interference Ratio (S Jonsson, Elias (TELEFONAKTI EBOLAGET LM ERI CSSON (pub |
| Content sources | 2004 |
| Journal sources | patno:EP1408635 the steps of:(verifying (5.40) a transmittedPower Control TF |
| Preferred web (1) Patent Offices (1) | verifying comprises weighting said pilot and data symbols, an command has been correctlyand giving a SIR estimation (5 Full text available at patent office. For more in-depth search |
| Other web | similar results Email, Save or Export checked results |
| File types * HTML (1) | |
| , | Sponsored links |
| O Refine your search | Data Verification |
| ep1408635epa02022734 | Solve the Problem of Validating Data Integration w/ DataXtend SI. www.progress.com/dataxtend |
| epb02022734 02022734 power control mobile unit | Data Standardization Quick To Build, Designed For Rapid Deployment & ROI. Find Out More. |
| transmitted powercode division | SilverCreekSystems.com/Standardize |
| transmission powerwireless communication | Vishay Weighing Systems Precise and repeatable – batch, blend, and mix weighing systems |
| more ⊳ | www.vishay.com |

| "tpc command" SiR verifying pilot data symbols weighting results on scirus.com, for scie | Page 2 of 2 |
|--|-------------|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| "tpc command" SiR verifying pilot data syn; Search | |
| | |
| | |

Downloads | Submit website | Scirus newsletter | Help | Library partners | Contact us

About us | Advisory board | Privacy policy | Terms & Conditions | Newsroom

Powered by FAST © Elsevier 2009

SCITUS for scientific information only

Advanced search | Preferences

| | | <u>Email, Save</u> or <u>Export</u> checked results Sor |
|---|---------|---|
| Filter search results by |] [] 1. | Method and device for estimating a Signal to Interference Ratio (S Jonsson, Elias (TELEFONAKTI EBOLAGET LM ERICSSON (pub |
| Content sources | | 2004 |
| Journal sources | No. | patno: EP1408635the steps of: (verifying (5.40) a transmittedPower Control TP |
| Preferred web (4) | 2. | verifying comprises weighting said pilot and data symbols, and command has been correctlyand giving a SIR estimation |
| ≈ Patent Offices (4) | | Full text available at patent office. For more in-depth search similar results |
| Other web | | Method and apparatus for classifying interference |
| File types | | Nilsson, Johan / Östberg, Christer / Eriksson, Hakan, EUROF |
| ■ HTML (4) | | patno: EP1221777internally for verifying , adjusting, orvoice, V, and data , D, tra |
| Ů Refine your search | | symbols (so-called pilotsat the common pilot channel (CPICH informationTransmission-Power-Control, TPC , command in the |
| mobile communications electronic circuit band-pass filter intermediate frequency classifying low-pass received communication high-frequency amplifier cut-off frequency automatic gain control more ⊳ | | input data via the port IN Full text available at patent office. For more in-depth search similar results |
| | 3. | Method and apparatus for classifying interference Nilsson, Johan / Ostberg, Christer / Eriksson, Hakan, UNITED TRADEMARK OFFICE PRE-GRANT PUBLICATION, Sep 2002 patno: US20020137485 |
| | | voice, V, and data, D, transmittedreceived known symbols (scommon pilot channel (CPICHvoice, V, and data, D, the information Control, TPC, command in the communicationsprocess of decorreceivedare added with a weight value that equals |
| | | Full text available at patent office. For more in-depth search similar results |
| | 4. | METHOD AND APPARATUS FOR CLASSIFYING INTERFERENCE NILSSON, Johan / ÖSTBERG, Christer / ERIKSSON, Håkan (ILM ERICSSON (publ)), PATENT COOPERATION TREATY APPLICATION WO02051044 |
| | | internally for verifying, adjusting, orvoice, V, and data, D, tra symbols (so-called pilotsat the common pilot channel (CPICH informationso-calledTransmission-Power-Control, TPC, comman communicationsreceives input data via the port IN Full text available at patent office. For more in-depth search similar results |
| | ş | |
| | E E | <u>mail, Save</u> or <u>Export</u> checked results |
| | | |
| | Spoi | nsored links |
| | Dat: | a Verification |

Data Verification

Solve the Problem of Validating **Data** Integration w/ DataXtend SI. www.progress.com/dataxtend

New Data Quality Wh Paper

Achieve data quality & consistency across your systems with Trillium www.trilliumsoftware.com

Data Standardization

"tpc command" SiR verifying pilot data symbols weight results on scirus.com, for scientif... Page 2 of 2


Quick To Build, Designed For Rapid Deployment & ROI. Find Out More.

SilverCreekSystems.com/Standardize

"tpc command" SiR verifying pilot data syn; | Search

Advanced search | Preferences

| | <u> </u> | Email, Save or Export checked results Sol | | | | |
|---|----------|--|--|--|--|--|
| Filter search results by | 1. | Mobile station apparatus and transmission power control method for Suzuki, Masaaki, FUJITSU LIMITED (Fujitsu Ltd.), EUROPEAN | | | | |
| Content sources | | 2007 | | | | |
| O Journal sources | | patno:EP1821426decision) 223 and a TPC command decision (hard decision) uni (Hardreceived signal (pilot signal) of theproviding received da | | | | |
| Preferred web (29) Patent Offices (27) NDLTD (2) | | in the TPC command decision unitplurality of TPC symbols (sto Full text available at patent office. For more in-depth search similar results | | | | |
| Other web (7) | 2. | Method and device for estimating a Signal to Interference Ratio (S | | | | |
| File types | | Jonsson, Elias (TELEFONAKTI EBOLAGET LM ERI CSSON (pub 2004 | | | | |
| R HTML (29) R PDF (6) PS (1) C Refine your search | | patno:EP1408635pilot and data symbols, characterisedPower Control TPC converifying comprises weighting said pilot and data symbols, and command has been correctlyand giving a SIR estimation (5 Full text available at patent office. For more in-depth search similar results | | | | |
| power control transmission power spreading factor control command wireless communication code division bearer radio transmission outer loop bit error more ⊳ | 3. | Method of decoding turbo-encoded data and receiver for decoding Maru, Tsuguo (NEC CORPORATION), EUROPEAN PATENT, May patno:EP1207625 | | | | |
| | | a target SIR, a comparatorcode, and a TPC command transf command to controlturbo-encoded data receivedinterference thenumber of a pilot symbol obtainedsynthesis. The weightin symbols, and computes | | | | |
| | | Full text available at patent office. For more in-depth search similar results | | | | |
| | 4. | OUTER LOOP POWER CONTROL FOR F-DPCH KAZMI, Muhammad / GERSTENBERGER, Dirk (TELEFONAKTI (PUBL); KAZMI, Muhammad; GERSTENBERGER, Dirk), PATE APPLICATION, Aug 2006 patno:W006081875equipment estimates the SIR every time slot andequipment c BER inequipment generates the TPC command for the downlink SIR target and sendscombining of the pilot symbols from all th Full text available at patent office. For more in-depth search | | | | |
| | | similar results | | | | |
| | 5. | Power control for mobile radio systems using perceptual speech querohani Mehdiabadi, Behrooz, Jan 2007List of Common Symbols xvii 1 IntroductionReceived Quality InterferenceList of Common Symbols a Gradient of aNpilot NumberrxTPCcmd Received TPC command R Transmissionfraused incoding gain ams Weighting factor calculated Full text thesis available via NDLTD (Australasian Digital Thesimilar results | | | | |
| | 6. | METHOD AND APPARATUS FOR COMMUNICATION CHANNEL ERRO ANDERSSON, Lennart / WANG, Yi-Pin, Eric / BOTTOMLEY, G (TELEFONAKTIEBOLAGET L M ERICSSON (publ); ANDERSSO Pin, Eric; BOTTOMLEY, Gregory, E.), PATENT COOPERATION T 2006 | | | | |



Sponsored links

Vishay Weighing Systems

Precise and repeatable - batch, blend, and mix weighing systems www.vishay.com

Free Database Download

Get the database that powers the world's most complex applications.

www.Objectivity.com

Database

Free Guide: How MySQL Powers Web 2.0

"tpc command" SiR pilot data symbols weighting results on scirus.com, for scientific info... Page 3 of 3

www.mysql.com

Previous 1 2 3 4

"tpc command" SiR pilot data symbols we; Search

Advanced search | Preferences

11-20 of 36 hits for "tpc command" SiR pilot data symbols weighting Email, Save or Export checked results Sor 11. COMBINED OPEN LOOP/CLOSED LOOP METHOD FOR CONTROLLING Filter search results by MOBILE STATION Shin, Sung-Hyuk / Lin, Zinan / Grieco, Donald M. / Olesen, F Content sources (INTERDIGITAL TECHNOLOGY CORPORATION), UNITED STAT 📖 Journal sources TRADEMARK OFFICE PRE-GRANT PUBLICATION, Sep 2008 patno:US20080220806 Preferred web (29) ...reception of wireless data. Additionally, the...PC) for both UL da channels...and sound reference symbols (SRS). UL channel...Alter Patent Offices (27) command signaling in DL control channel...MCS; and a is a weigh NDLTD (2) enable...power controlled data channel as a reference... Other web (7) Full text available at patent office. For more in-depth search similar results File types HTML (29) 12. report-book-2e-sample-chaps.dvi [PDF-2MB] PDF (6) Jul 2008 PS (1) ...22 1.2.6.1 Downlink Pilot-Assisted Channel Estimation...23 1.2.0 Assisted Channel Estimation 24 1.2.6.3 Pilot-Symbol Assist 🖰 Refine your search a 4.1 Kbps Data Service to the DL DPDCH in FDD... [http://eprints.ecs.soton.ac.uk/14586/1/report-book-2e-...] power control similar results transmission power spreading factor 13. Method and apparatus for communication channel error rate estimate control command Andersson, Lennart / Wang, Yi-Pin Eric / Bottomley, Gregor wireless communication PATENT AND TRADEMARK OFFICE PRE-GRANT PUBLICATION, Nov code division bearer patno:US20060262754 radio transmission ...determining whether the SIR estimated for the...above or below outer loop SIR-to-CER mapping relationship...are transmitted as symbols. M bit error a two-bit TPC command symbol. Assuming...from the Common P more a received... Full text available at patent office. For more in-depth search similar results 14. Determination of a channel estimate of a transmission channel Jonsson, Elias / Nilsson, Johan / Lindoff, Bengt, UNITED STA TRADEMARK OFFICE PRE-GRANT PUBLICATION, Mar 2007 patno:US20070072552 ...for estimating a SIR. The receiver...207, a common pilot estima symbols Du which are fed to a...then fed into a SIR estimation ur factors allowing...determined by the SIR unit 210 and determines. command as the result... Full text available at patent office. For more in-depth search similar results 15. 3GPP W-CDMA Design Library September 2004 ii Notice The inform Aug 2004 ...the U. S. Government is subject to restrictions as set forth in sul Rights in Technical Data and Computer Software clause at DFARS agencies, and subparagraphs (c) (1) and (c) (2) of the... [http://newport.eecs.uci.edu/eceware/ads_docs/pdf/wcdma...] similar results 16. Microsoft Word - D4.2.2.doc [PDF-2MB] Feb 2008 ...98 5.3.6.1 CQI channel data rate...101 5.3.7.1 CQI data proces structure...vs. network size 21 Figure 2-5: The SIR distribution of [http://www.imperial.ac.uk/membrane/documents/Deliverab...]


| | similar results |
|---------------|--|
| 17. | Power control circuit and radio transmission apparatus Harada, Hiroshi / Nakano, Yoshikazu (Fujitsu Limited), UNIT TRADEMARK OFFICE GRANTED PATENT, Feb 2008 patno:US7336751transmits information data through the Itransmits control data control data has respective regions of a pilot symbol (Pilotillust the number0 means that a TPC command is on or off Full text available at patent office. For more in-depth search similar results |
| 18. | 2008:218 CIV M A S T E R 'S T H E S I S Uplink Baseband Encoder Dec 2008offline fashion. The data will include informationlimited amoun to be repeated and thisCore Network CPICH Common Pilot Chan ProcessingDPDCH Dedicated Physical Data Channel vii DSP Digit Number SI R Signal-to-Interference [http://epubl.luth.se/1402-1617/2008/218/LTU-EX-08218-S] similar results |
| 19. | Radio Resource Management Content of the lecture • Changing cape Feb 2002estimates the received SIR and compares it with required SIR to from the pilot symbols of the DL-DPCH • MS transmits the TPC cavailableand 1 dB step size Data DataTPC TPCI Pilot [http://www.comlab.hut.fi/opetus/238/lecture10_RRM.pdf] more hits from [www.comlab.hut.fi] similar results |
| 20. | Method of decoding turbo-encoded data and receiver for decoding Maru, Tsuguo (NEC Corporation), UNITED STATES PATENT AND GRANT PUBLICATION, Jun 2002 patno:US20020080510measured SIR to a target SIR, a comparatorcode, and a TPC transmitterturbo-encoded data receivesinterference ratio (SIR pilot symbol obtained0071] The weighting processorof pilot Full text available at patent office. For more in-depth search similar results |
| Spon | sored links |
| Comr Explo | mand Golf are 100+ Golf Choices. Deals on Command Golf! BizRate.com |
| | hing and Dosing hing, Mixing, Batching, Filling Wiegen, Dosieren, Mischen, Abfüllen |
| www | .gbuettner.de |
| Save | Commander at Amazon on pilot commander! Qualified orders over \$25 ship free zon.com |
| | Previous 1234 |

"tpc command" SiR pilot data symbols weighting results on scirus.com, for scientific info... Page 3 of 3

"tpc command" SiR pilot data symbols we Search
Back to top

Advanced search | Preferences

| 21-30 01 30 IIIIS 101 TPC COIIII | | pilot data symbols weighting mail, <u>Save</u> or <u>Export</u> checked results Sor |
|---|------------|--|
| Filter search results by | | Transmission power control apparatus |
| Content sources | | Nakamura, Satoshi / Minowa, Morihiko / Kawaguchi, Noriyu Kubo, Tokuro / Kimura, Dai (Fujitsu Limited), <i>UNITED STATE</i> |
| Journal sources | | OFFICE GRANTED PATENT, Jun 2006 patno:US7062287 |
| Preferred web (29) * Patent Offices (27) | | Accordingly, the SIR measurement unitestimates receive SIR symbols included in one slot. A target-SIR setting unit 53into tr transmitsis ± 40 dB, a TPC command is generated 1600 |
| ■ NDLTD (2) | ~ | Full text available at patent office. For more in-depth search similar results |
| Other web (7) | 22. | Radio Resource Management Content of the lecture • Changing cap |
| File types # HTML (29) PDF (6) PS (1) Chapter of Refine your search | | Feb 2002estimates the received SIR and compares it with required SIR to from the pilot symbols of the DL-DPCH • MS transmits the TPC c availableand 1 dB step size Data DataTPC TPCI Pilot [http://www.comlab.hut.fi/opetus/238/lecture10_RRM.pdf] more hits from [www.comlab.hut.fi] |
| power control transmission power spreading factor control command wireless communication code division bearer | 23. | Method of decoding turbo-encoded data and receiver for decoding Maru, Tsuguo (NEC Corporation), UNITED STATES PATENT AND GRANT PUBLICATION, Jun 2002 patno: US20020080510measured SIR to a target SIR, a comparatorcode, and a TPC |
| ■ radio transmission ■ outer loop ■ bit error more ⊳ | | transmitterturbo-encoded data receivesinterference ratio (SIF pilot symbol obtained0071] The weighting processorof pilot Full text available at patent office. For more in-depth search similar results |
| | 24. | Method and apparatus for transmit power control Wang, Yi-Pin Eric / Bottomley, Gregory / Andersson, Lennar AND TRADEMARK OFFICE PRE-GRANT PUBLICATION, Nov 2006 patno: US20060262840and may not carry pilot or reference informationhave a high e reliable data-based signal qualitymay comprise a pilot signal ha symbols and (referencecomprises an uplink TPC command ger Full text available at patent office. For more in-depth search similar results |
| | 25. | METHODS, RECEIVERS, AND COMPUTER PROGRAM PRODUCTS FOR TRANSMISSION POWER CONTROL COMMANDS USING BIASED INT BERNHARDSSON, Bo / NILSSON, Johan / JONSSON, Elias / I (TELEFONAKTIEBOLAGET LM ERICSSON (publ)), PATENT COCAPPLICATION, Apr 2004 patno: WO04026483base station transmits a TPC command to decrease the mobile. TPC command that was transmitted byto Interference Ratio (SI channeltransmitted. Accordingly, the TPC command received (command that a patent office. For more in-depth search similar results |
| | 26. | TRANSMISSION POWER CONTROLLER NAKAMURA, Satoshi Fujitsu Limited / MINOWA, Morihiko Fu Tokuro Fujitsu Limited / SAWADA. Kensuke Fujitsu Limited / |



Precise and repeatable - batch, blend, and mix **weighing** systems www.vishay.com

Walz Scale

Weighing Equipment & Service ISO 17025 Accredited

"tpc command" SiR pilot data symbols weighting results on scirus.com, for scientific info... Page 3 of 3

www.walzscale.com

Weighing and Dosing Weighing, Mixing, Batching, Filling Wiegen, Dosieren, Mischen, Abfüllen www.gbuettner.de

Previous <u>1 2 3 4</u>

"tpc command" SiR pilot data symbols we, Search

Advanced search | Preferences

| ······································ | | pilot data symbols weighting mail, Save or Export checked results |
|---|------------|--|
| | m E | Sor |
| Filter search results by | 31. | Diversity detection for WCDMA |
| Content sources | | Dabak, Anand G. / Hosur, Srinath / Kinjo, Shigenori / Gathe Instruments Incorporated), UNITED STATES PATENT AND TRAI |
| Journal sources | | PATENT, Oct 2004 patno: US6804311 |
| Preferred web (29) Patent Offices (27) | | slot includes pilot symbols 740, data symbols 746 andschel are transmittedkeyed (QPSK) known data in predeterminedcir TPC symbols , RI symbols and data symbols on leads |
| NDLTD (2) | | Full text available at patent office. For more in-depth search |
| Other web (7) | | similar results |
| File types * HTML (29) | 32. | Power control circuit and radio transmission apparatus Harada, Hiroshi / Nakano, Yoshikazu, UNITED STATES PATEN PRE-GRANT PUBLICATION, Jun 2003 |
| PDF (6) PS (1) | | patno: US20030103577 |
| ੈ Refine your search | | transmits information data through the Itransmits control dat control data has respective regions of a pilot symbol (Pilot illust the number0 means that a TPC command is on or off |
| | - | Full text available at patent office. For more in-depth search |
| power controltransmission power | | similar results |
| spreading factor control command wireless communication code division bearer radio transmission outer loop bit error more ⊳ | 33. | STTD encoding for PCCPCH Dabak, Anand Ganesh / Schmidl, Timothy M. / Hosur, Srinat AND TRADEMARK OFFICE PRE-GRANT PUBLICATION, Dec 2004 patno: US20040252796 |
| | | switches SW0 and SW1 selectively multiplex SCH data with BCH response to a control signal on leadmultiplex circuit 118 multiple symbols 302 with OTD encoded pilot symbols 304. The pilot sy Full text available at patent office. For more in-depth search similar results |
| | 277777 0 4 | |
| | 34. | control commands using biased interpretation Nilsson, Johan / Jonsson, Elias / Bernhardsson, Bo / Lindof PATENT AND TRADEMARK OFFICE PRE-GRANT PUBLICATION, Mar patno: US20040058700 |
| | | that the TPC symbols may includetypes of data transmitted command. [0037] The TPC command producedthe user data weighting factors andcorresponds to the TPC command receive be mapped |
| | | Full text available at patent office. For more in-depth search similar results |
| | 35. | STTD encoding for PCCPCH Dabak, Anand Ganesh / Schmidl, Timothy M. / Hosur, Srinat Incorporated), UNITED STATES PATENT AND TRADEMARK OFFICE 2004 |
| | | patno:US6728302switches SW0 and SW1 selectively multiplex SCH data with BCH response to a control signal on leadmultiplex circuit 118 multiple symbols 302 with OTD encoded pilot symbols 304. The pilot sy Full text available at patent office. For more in-depth search similar results |
| | 36 | Microsoft Word - UTRA.doc [PDF-2MB] |

Oct 1998

...physical layer) L2 Layer 2 (**data** link layer) L3 Layer 3 (network. Protocol **Data** Unit PHY Physical layer PhyCH...Dedicated Control C Unit SF Spreading Factor **SIR** Signal-to-Interference Ratio... [http://www.comlab.hut.fi/opetus/238/utra.pdf] similar results

Email, Save or Export checked results

Sponsored links

<u>Vishay Weighing Systems</u>

Precise and repeatable - batch, blend, and mix weighing systems www.vishay.com

Free Database Download

Get the database that powers the world's most complex applications.

www.Objectivity.com


Database

Free Guide: How MySQL Powers Web 2.0

www.mysql.com

Previous 1234

"tpc command" SiR pilot data symbols we, Search



Correspondence Address for 10/530370

| Customer Number | Contact Information | | Address | |
|--------------------------------------|---|-----------|---|----------------|
| 27045 Delivery Mode: <u>Paper</u> | Telephone: (972)583-5497 Fax: No Fax # E-Mail: melissa.wingo@ericss | on.com | ERICSSON IN 6300 LEGAC M/S EVR 1-C PLANO TX 7: | Y DRIVE -11 |
| Appln Info Contents | Petition Info Atty/Agent I | Info Con | ntinuity/Reexam | Foreign I |
| Search Another: A | pplication # Search | or Pate | nt# | Search |
| PCT / | / Search | or PG PUI | BS# | |
| Attorne | y Docket # | Se | earch | |
| Bar Coo | le# | arch | | |

To go back, right click here and select Back. To go forward, right click here and select Forward. To refresh, right click here and select Refresh.

Back to OASIS | Home page

Continuity/Reexam Information for 10/530370

Parent Data

10530370, filed 09/19/2005 and having 1 RCE-type filing therein is a national stage entry of PCT/EP03/09208, International Filing Date: 08/20/2003 claims foreign priority to 020227344, filed 10/11/2002 claims foreign priority to 60418912, filed 10/16/2002

| Child Data Appln Info Contents Petition Info At | y/Agent Info Continuity/Reexam Foreign Data |
|---|---|
| Search Another: Application # | or Patent# Search |
| PCT / / Se | or PG PUBS # |
| Attorney Docket # | Search |
| Bar Code # | Search |

To go back, right click here and select Back. To go forward, right click here and select Forward. To refresh, right click here and select Refresh.

Back to OASIS | Home page

Foreign Information for 10/530370

| Priority# | Date | Country |
|-----------|------------|------------------------------|
| 60418912 | 10/16/2002 | UNITED STATES OF AMERICA |
| 020227344 | 10/11/2002 | EUROPEAN PATENT OFFICE (EPO) |

| Appln Info Contents Petition Info | Atty/Agent Info Continuity/Reexam Pareign Data |
|---------------------------------------|--|
| Search Another: Application # Search | or Patent# Search |
| PCT / / | Search Search Search |
| Attorney Docket # | Search |
| Bar Code # | Search |

To go back, right click here and select Back. To go forward, right click here and select Forward. To refresh, right click here and select Refresh.

Back to OASIS | Home page

Inventor Information for 10/530370

| Inventor Name | City | State/Country SWEDEN | |
|--------------------------------------|---------------------|---------------------------|--|
| JONSSON, ELIAS | MALMO | | |
| Appln Info Contents Petition Info | Atty/Agent Info | Continuity/Reexam Foreign | |
| Search Another: Application # Search | or P | Patent# Search | |
| PCT / | Search or PG Search | PUBS # | |
| Attorney Docket # | | Search | |
| Bar Code # | Search | | |

To go back, right click here and select Back. To go forward, right click here and select Forward. To refresh, right click here and select Refresh.

Back to $\ \underline{OASIS}\ |\ Home\ page$



Day: Thursday

Date: 9/3/2009 Time: 09:20:15

Inventor Name Search Result

Your Search was:

Last Name = JONSSON First Name = ELIAS

| Application# | Patent# | PG Pub# | Status | Date Filed | Title | Examiner Name |
|--------------|---------|-------------|--------|------------|---|---------------|
| 10368873 | 7162262 | 20040058699 | 150 | 02/19/2003 | METHODS, SYSTEMS AND COMPUTER PROGRAM PRODUCTS FOR REQUESTING RECEIVED POWER LEVELS BASED ON RECEIVED BLOCK ERROR RATES UTILIZING AN ANTI-WINDUP AND/OR EMERGENCY PROCEDURE | SHARMA,SUJATH |
| 10426254 | 7239677 | 20040218698 | 150 | 04/29/2003 | METHOD AND APPARATUS FOR SOFT SYMBOL SCALING | BENGHUZZI,MOH |
| 10445759 | 7184791 | 20040058700 | 150 | 05/27/2003 | METHODS, RECEIVERS, AND COMPUTER PROGRAM PRODUCTS FOR DETERMINING TRANSMISSION POWER CONTROL COMMANDS USING BIASED INTERPRETATION | AMINZAY,SHAIM |
| 10457913 | 7177602 | 20040058657 | 150 | 06/10/2003 | ELECTRONIC DEVICES HAVING AUTOMATIC FREQUENCY | NGUYEN,THUAN |

| | | | | | CONTROL SYSTEMS AND METHODS AND COMPUTER PROGRAM PRODUCTS FOR OPERATING THE SAME | |
|----------|---------------|-------------|-----|------------|---|---------------|
| 10499071 | 7366230 | 20050143112 | 150 | 06/15/2004 | POWER CONTROL IN MOBILE RADIO COMMUNICATIONS SYSTEMS | WONG,LINDA |
| 10523987 | 7466658 | 20060103587 | 150 | 10/21/2005 | RECEIVER AND METHOD FOR DECODING OF TRUNCATED DATA | LIU,BEN |
| 10527366 | 7555077 | 20050271122 | 150 | 07/27/2005 | METHOD FOR PATH-SEARCHER SCHEDULING | DSOUZA,JOSEPH |
| 10527896 | 7558314 | 20060140255 | 150 | 09/28/2005 | METHOD AND DEVICE FOR DETECTION OF A UMTS SIGNAL | TRAN,KHANH |
| 10530370 | Not Issued | 20060014487 | 71 | 09/19/2005 | Method and device for estimating a signal to interference ratio (SIR) in Wideband Code Division Multiple Access (WCDMA) systems | TORRES,JUAN |
| 10542671 | Not Issued | 20060274819 | 83 | 12/28/2005 | Truncation and level adjustment of rake output symbols | MALEK,LEILA |
| 10557137 | 7561637 | 20070072552 | 150 | 07/09/2006 | DETERMINATION OF A CHANNEL ESTIMATE OF A TRANSMISSION CHANNEL | PATEL,DHAVAL |
| 10595115 | Not Issued | 20070195864 | 41 | 08/16/2006 | Positioning of a path searcher window in a cdma receiver | GUARINO,RAHEL |
| 10608241 | Not Issued | 20040066841 | 161 | 06/27/2003 | Systems, methods of operating, and computer program products for selecting delays for a rake | BURD,KEVIN |

| | | | | | receiver based on signal to interference ratios and/or powers | |
|----------|---------------|-------------|-----|------------|---|----------------|
| 10679439 | 7474648 | 20040259576 | 150 | 10/07/2003 | FILTERING MULTIPATH PROPAGATION DELAY VALUES FOR USE IN A MOBILE COMMUNICATIONS SYSTEM | VO,NGUYEN |
| 10763755 | 7376195 | 20050163200 | 150 | 01/23/2004 | DIGITAL COMMUNICATION SYSTEMS HAVING DECREASED MEMORY | HA,DAC |
| 10799322 | Not Issued | 20050201499 | 41 | 03/12/2004 | Method and apparatus for received signal quality estimation | FLORES,LEON |
| 10800167 | 7539240 | 20050201447 | 150 | 03/12/2004 | METHOD AND APPARATUS FOR PARAMETER ESTIMATION IN A GENERALIZED RAKE RECEIVER | FOTAKIS,ARISTO |
| 11305128 | Not Issued | 20060234755 | 41 | 12/19/2005 | Cell selection in broadcast and multicast communication environments | NGUYEN,TU |
| 11446734 | Not Issued | 20070280368 | 71 | 06/05/2006 | Method and apparatus for correcting data transmission errors | DSOUZA,JOSEPH |
| 11679541 | Not Issued | 20080205562 | 30 | 02/27/2007 | Method and Apparatus for Impairment Correlation Estimation in MIMO Systems | GHAYOUR,MOHA |
| 11721582 | Not Issued | 20080008228 | 30 | 07/17/2007 | Scaling in a Receiver for Coded Digital Data Symbols | GHAYOUR,MOHA |
| 11721938 | Not Issued | | 19 | 01/01/0001 | Method and Device for Power Control | , |
| 11743298 | Not Issued | 20080273608 | 30 | 05/02/2007 | Method and Apparatus for Correcting IQ Imbalance in an OFDM Receiver | GHAYOUR,MOHA |
| I | II I | II I | l | | | I |

| 11751109 | Not Issued | 20080291978 | 30 | 05/21/2007 | Receiver Parametric Covariance Estimation for Transmit Diversity | GHAYOUR,MOHA |
|----------|---------------|-------------|----|------------|---|--------------|
| 11752014 | Not Issued | 20080291981 | 30 | 05/22/2007 | Method and Apparatus for Removing Pilot Channel Amplitude Dependencies from RAKE Receiver Output | GHAYOUR,MOHA |
| 11755887 | Not Issued | 20080298510 | 30 | 05/31/2007 | Memory-Saving Method for Generating Soft Bit Values from an OFDM Signal | GHAYOUR,MOHA |
| 11756172 | Not Issued | 20080298227 | 30 | 05/31/2007 | Method for Interference Estimation for Orthogonal Pilot Patterns | MERED,HABTE |
| 11762982 | Not Issued | 20080310562 | 30 | 06/14/2007 | Efficient Covariance Computation by Table Lookup | GHAYOUR,MOHA |
| 11856233 | Not Issued | 20090075647 | 30 | 09/17/2007 | UE Measurement Scheduling Based on Measurement Bandwidth | URBAN,EDWARD |
| 11858548 | Not Issued | 20080013603 | 30 | 09/20/2007 | Receiver and A Receiving Method | GHAYOUR,MOHA |
| 12065508 | Not Issued | 20090041163 | 30 | 07/16/2008 | Selecting Delay Values for a RAKE Receiver | GHAYOUR,MOHA |
| 12107623 | Not Issued | 20090149147 | 25 | 04/22/2008 | Speed-Based, Hybrid Parametric/Non- parametric Equalization | , |
| 12133636 | Not Issued | 0 | 30 | 06/05/2008 | Method and Apparatus for Efficient Estimation of Interference in a Wireless Receiver | GHAYOUR,MOHA |
| 12198973 | Not Issued | 0 | 25 | 08/27/2008 | NONPARAMETRIC MIMO G-RAKE RECEIVER | , |
| 12239918 | Not Issued | 0 | 25 | 09/29/2008 | RECEIVER AND METHOD FOR PROCESSING | , |

| | | | | | RADIO SIGNALS USING SOFT PILOT SYMBOLS | |
|----------|---------------|---|-----|------------|--|--------------|
| 12278379 | Not Issued | 0 | 25 | 09/29/2008 | METHOD AND DEVICE FOR CHANNEL RESPONSE DETERMINATION | , |
| 12296444 | Not Issued | | 19 | 01/01/0001 | Controlling a Power Level in a Wireless Communications System with Different Scrambling Codes | , |
| 12391371 | Not Issued | 0 | 30 | 02/24/2009 | Method for Allocating Rake Fingers in Multi- Carrier Systems | GHAYOUR,MOHA |
| 12391796 | Not Issued | 0 | 25 | 02/24/2009 | Estimating the Ratio of Traffic Channel Power to Pilot Power in a MIMO Wireless Communication System | , |
| 12408939 | Not Issued | | 19 | 03/23/2009 | Signal Reception with Adjustable Processing Delay Placement | , |
| 12414202 | Not Issued | 0 | 25 | 03/30/2009 | Automatic Gain Control in Multi- Carrier Wireless Systems | , |
| 12423480 | Not Issued | 0 | 20 | 04/14/2009 | Method and Appratus for Direct Estimation of Impairment Correlations for Received Signal Processing | , |
| 12472742 | Not Issued | 0 | 20 | 05/27/2009 | Method and Apparatus for Allocating Processing Delays in Multi-Carrier Systems | , |
| 12477168 | Not Issued | 0 | 20 | | Method and Apparatus for Allocating Processing Delays in Multi-Carrier Systems | , |
| 60346745 | Not Issued | | 159 | | Power control in mobile radio | , |

| | | | | communications systems | |
|----------|---------------|-----|------------|--|---|
| 60404718 | Not Issued | 159 | | Selecting a rounded estimate in a receiver of coded digital data symbols | , |
| 60412375 | Not Issued | 159 | | Method for path- searcher scheduling | , |
| 60412896 | Not Issued | 159 | | AFC-algorithm with compensation for hardware imperfections | , |
| 60412897 | Not Issued | 159 | | Anti-windup and emergency procedures for outer loop power controllers using filtered block error rates for WCDMA | , |
| 60412898 | Not Issued | 159 | 09/23/2002 | TPC decoding | , |

Search and Display More Records.

Search Another: Inventor

Last Name

JONSSON

First Name

ELIAS

Search

To go back use Back button on your browser toolbar.

Back to PALM | ASSIGNMENT | OASIS | Home page



PALM INTRANET

Day: Thursday

Date: 9/3/2009 Time: 09:20:34

Inventor Name Search Result

Your Search was:

Last Name = JONSSON First Name = ELIAS

| Application# | Patent# | PG Pub# | Status | Date Filed Title | | Examiner Name | Inventor Name |
|--------------|---------------|------------|--------|------------------|--|------------------|-------------------|
| 60412899 | Not Issued | | 159 | 09/23/2002 | Objective multi-path delay selection algorithm for WCDMA | , | JONSSON, ELIAS |
| 60414055 | Not Issued | | 159 | 09/27/2002 | Method and device for detection of a signal | , | JONSSON, ELIAS |
| 60418912 | Not Issued | | 159 | | Method and device for estimating a signal to interference ratio | , | JONSSON, ELIAS |
| 60431552 | Not Issued | | 159 | 12/05/2002 | TPC deconding in soft handover | , | JONSSON, ELIAS |
| 60444778 | Not Issued | | 159 | 02/04/2003 | Optimal scaling of RAKE output symbols for WCDMA | , | JONSSON, ELIAS |
| 60472483 | Not Issued | | 159 | 05/21/2003 | Method and apparatus for improved DPCH SIR estimation | , | JONSSON, ELIAS |
| 60479054 | Not Issued | | 159 | 06/16/2003 | Positioning a multipath search window | , | JONSSON, ELIAS |
| 60479151 | Not Issued | | 159 | 06/18/2003 | Filtering multipath propagation delay values for use in a mobile communications system | , | JONSSON, ELIAS |
| 60482673 | Not Issued | | 159 | 06/26/2003 | Method and device for detection of a signal | , | JONSSON, ELIAS |
| 60500413 | Not Issued | | 159 | | Positioning of a path searcher window | , | JONSSON, ELIAS |
| 60638268 | Not Issued | | 159 | | Method and device for power control | , | JONSSON, ELIAS |
| 60638438 | Not | | 159 | 12/22/2004 | Scaling in a receiver | , | JONSSON, |

Search

| | Issued | | | for coded digital data symbols | | ELIAS |
|----------|---------------|-----|------------|---|---|-------------------|
| 60671099 | Not Issued | 159 | 04/14/2005 | Cell selection for MBMS | , | JONSSON, ELIAS |
| 60719037 | Not Issued | 159 | 09/21/2005 | Selecting delay values for a rake receiver | , | JONSSON, ELIAS |
| 60744673 | Not Issued | 159 | 04/12/2006 | Controlling a power level in a wireless communications system with different scrambling codes | , | JONSSON, ELIAS |
| 60771855 | Not Issued | 159 | 02/10/2006 | Channel estimator and method for channel estimation | , | JONSSON, ELIAS |
| 61012544 | Not Issued | 159 | 12/10/2007 | Hybrid Parametric/Non- parametric Equalization | , | JONSSON, ELIAS |
| 61073264 | Not Issued | 159 | 06/17/2008 | SOFT PILOT SYMBOLS IN A DIGITAL COMMUNICATION SYSTEM | , | JONSSON, ELIAS |
| 61143248 | Not Issued | 20 | 01/08/2009 | Fixed Grid Activation | , | JONSSON, ELIAS |
| 61143534 | Not Issued | 20 | 01/09/2009 | Fixed Grid Activation | , | JONSSON, ELIAS |

Inventor Search Completed: No Records to Display.

Search Another: Inventor JONSSON First Name

ELIAS

To go back use Back button on your browser toolbar.

Back to PALM | ASSIGNMENT | OASIS | Home page